

## TEMPERATURE, REMOTE BULB HONEYWELL, JOHNSON

FAX 610-789-7300

WWW.NECCDELIVERS.COM

## 800-227-9800





Fast Response and Averaging



Well Mount



Commercial temperature controls provide flexibility to electrical systems. Configurations are available for duct, wall or pipe mounting with many temperature and switch arrangements for whatever purpose your system requires. For ease of selection, we have put the most popular Honeywell and Johnson Controls models in two handy selection charts below. For your convenience, we have listed each in order by temperature range.

HONEYWELL TEMPERATURE CONTROLLERS					
ORDER #	RANGE	DIFFERENTIAL	SWITCH	SENSOR	
T6031A1029	-30–90°F	3.5–16	SPDT	8' cap	
T6031A1060	-30–90°F	3.5–16	SPDT	20' cap	
T6054A1005	-30–100°F	3.5	SPDT	Coiled	
T675A1508	0-100°F	3–10	SPDT	5' cap	
T675A1516	0-100°F	1	SPDT	5' cap	
T675A1565	0-100°F	3–10	SPDT	20' cap	
T675A1706	0-100°F	3–10	SPDT	5' fast response	
T678A1437	0-100°F	3–10	2 SPDT	5' cap	
T678A1478	0-100°F	3–10	2 SPDT	5' fast response	
T6031C1009	40–180°F	2	SPDT	5½′ cap	
L6006C1018	65–200°F	5–30	SPDT	Strap-on (changeover)	
L6006A1145	100–240°F	5–30	SPDT	Well mount	
L6008A1192	100–240°F	5–30	SPDT	5' cap	

JOHNSON CONTROLS TEMPERATURE CONTROLLERS						
ORDER #	RANGE	DIFFERENTIAL	SWITCH	SENSOR		
A19ABC-24	-30–100°F	3–12	SPDT	8' cap		
A19ABC-36	-30–100°F	3–12	SPDT	20′ cap		
A19BBC-2	-30–100°F	3–12	SPDT	Coiled		
A28AA-29	-30–100°F	5	2 SPDT	8' cap		
A19AAA-18	30–110°F	3½	SPDT	12' averaging		
A19AAF-12	25–225°F	3½	SPDT	10″ cap		
A28AA-4	30–110°F	3½	2 SPDT	Coiled		
A11B-1	35–45°F	8	SPDT	20′ cap		
A19CAC-2	60–90°F	10	SPDT	Strap-on (changeover)		
A19ABC-11	100–240°F	6–24	SPDT	Well mount		
A19ABC-12	100–240°F	6–24	SPDT	8' cap		
A19DAC-1	100–240°F	10	SPDT	Strap-on		

**NOTE:** Other ranges, switch configurations and brands such as Barber-Colman and White-Rodgers are cross-referenced in our database and quickly available.



Coiled Bulb