

FAX 610-789-7300
WWW.NECCDELIVERS.COM
800-227-9800

Barber-Colman Remote Bulb Controls



Barber-Colman remote bulb temperature controls come in a variety of styles and control signals to control a sensed media in ducts, pipes, boilers, tanks, outdoor or any applications where you want the control outside the existing condition. These controls come in a variety of sensing bulbs and lengths. Models with one switch, multiple switches and proportioning modes of control are available.

ORDERING INFORMATION						
ORDER #	RANGE	SWITCH	DIFFERENTIAL	ELEMENT		
TC-4111	-40 to 120°F	SPDT	3-16°F	6' cap.		
TC-4111-020				20' cap.		
TC-4121		2-SPDT	2-10°F	10' armored		
TC-4211	0 to 160°F	SPDT	1-15°F	6' cap.		
TC-221				10' armored		
TC-202	10 to 90°F	2-SPDT	0-20°F	6' cap.		
TC-252						
TC-282		3-SPDT				
TC-288		4-SPDT Cool Only				
TP-202	34 to 60°F	SPDT Prop. Feedback	4-12°F	52" averaging		
TP-402						
TC-5131	50 to 90°F	SPDT Auto Reset	5°F	20' cap.		
TC-5141						
TC-4166	50 to 210°F	SPDT	2°F	Coiled		
TC-2974			10°F	Strap-on		
TP-209	50 to 130°F	SPDT Prop. Feedback	4-12°F	6' cap.		
TA-3432	75 to 135°F	SPDT Manual Reset	10°F	7½' Helical Bimetal		
TP-204	100 to 180°F	SPDT Prop. Feedback	4-12°F	6' cap.		
TC-4112	100 to 260°F	SPDT	3-16°F			
TC-4122					10' armored	

Outdoor Reset Temperature Controls



This control provides a simple method of changing the controlled setpoint in relation to the outdoor temperature. One bulb senses the controlled media, the second bulb senses the outdoor air temperature. The temperature of the controlled media increases as the outdoor air temperature decreases, thus providing only the minimum heat necessary for the ambient conditions. This results in decreased heat loss and results in considerable energy savings.

ORDERING INFORMATION					
ORDER #	DIFFERENTIAL	SWITCH	RANGE	ELEMENT	FEATURES
TC-4151	2-10°F	SPDT	70-120°F	30' cap.	1:1.5 Ratio
TC-4152	3-16°F				1:1 Ratio
TC-4251	2-7°F	2-SPDT	60-120°F	15' in / 30' out	1:1.5 Ratio
TC-4252	2-10°F				1:1 Ratio
TP-231	5-25°F	SPDT Prop. Feedback	70-130°F	15' in / 30' out	1:1.5 Ratio
TP-232	4-12°F		60-120°F		1:1 Ratio