



NEW! Combination Industrial Thermometer And 100 Ohm RTD Temperature Sensor

A Direct Replacement Exact Fit!

Features:

- Goes right back in the thermometer well you're currently using
- RTD sensor built-in. No need to add a new well
- Ranges to 500°F
- RTD connection is water- and weather-resistant
- Adjustable angle for easy reading

ORDERING INFORMATION

ORDER # (3.5" STEM)	ORDER # (6" STEM)	RANGE
A00501RTD100	A00601RTD100	-40 to 110°F
A00502RTD100	A00602RTD100	0 to 100°F
A00506RTD100	A00606RTD100	30 to 180°F
A00508RTD100	A00608RTD100	30 to 300°F

Aluminum stem models shown are for new or existing well installation. Direct immersion brass stem models also available.

NEW! Combination Bimetal Dial Thermometer And RTD Temperature Sensor



Now when you automate, you can add electronic temperature status feedback without any major modifications. Just replace your existing dial thermometer with a new Twin-Temp Combination RTD/Dial Thermometer. It goes right back in the 1/2" thread well you're presently using. No need to repipe or add wells. Available in rigid stem back mount or adjustable angle. Use in wells, storage tanks, boilers, heat transfer or any place where you want electronic data acquisition and local visual indication. 3" dial models shown below; 5" dial face also available.

ORDERING INFORMATION

RANGE °F	STEM	100 ohm		1000 ohm	
		3" Adjustable	3" Back Mount	3" Adjustable	3" Back Mount
-100 to 150	2.5"	32025A201G4RA	30025A201G4RA	32025A201G4RC	30025A201G4RC
0 to 250		32025A206G4RA	30025A206G4RA	32025A206G4RC	30025A206G4RC
50 to 400		32025A209G4RA	30025A209G4RA	32025A209G4RC	30025A209G4RC
-100 to 150	4"	32040A201G4RA	30040A201G4RA	32040A201G4RC	30040A201G4RC
0 to 250		32040A206G4RA	30040A206G4RA	32040A206G4RC	30040A206G4RC
50 to 400		32040A209G4RA	30040A209G4RA	32040A209G4RC	30040A209G4RC
-100 to 150	6"	32060A201G4RA	30060A201G4RA	32060A201G4RC	30060A201G4RC
0 to 250		32060A206G4RA	30060A206G4RA	32060A206G4RC	30060A206G4RC
50 to 400		32060A209G4RA	30060A209G4RA	32060A209G4RC	30060A209G4RC

Stem: 304 S.S.

Crystal: Glass

Connection: 1/2" NPT

Available Options (allow extra order time):

- Thermocouple sensor types J, K, E, T
- Waterproof housing
- Dual scale