

Belimo Motorized Butterfly Valves

This order chart shows the available sizes and capacities of the Belimo butterfly valve assemblies. Select the valve you want and pick the Belimo actuator needed for the service you require.



Belimo Two-Way Butterfly Valves

- Fully replaceable EPDM seat for bubble-tight seal and flange seal
- 416 stainless steel shaft
- Built-in flange gasket
- Your choice of electronic actuators, spring and non-spring return

2 WAY VALVE ORDERING INFORMATION			
SIZE	ORDER#	90° Cv	60° Cv
2	F650	115	44
2.5	F665	196	75
3	F680	302	116
4	F6100	600	230
5	F6125	1022	392
6	F6150	1579	605
8	F6200	3136	1202
10	F6250	5340	2047
12	F6300	8250	3162

Belimo Three-Way Butterfly Valves

- Six possible valve configurations available
- ANSI rated bodies
- Mixing or diverting applications

3 WAY VALVE ORDERING INFORMATION			
SIZE	ORDER#	90° Cv	60° Cv
2	F750	115	44
2.5	F765	196	75
3	F780	302	116
4	F7100	600	230
5	F7125	1022	392
6	F7150	1579	605
8	F7200	3136	1202
10	F7250	5340	2047
12	F7300	8250	3162



Belimo Actuators

Select the signal and torque you need for your application or contact us and we'll engineer an assembly for you.

Non-Spring return actuators shown. Spring return, auxiliary switches and other options available on request. When ordering MAR series, please specify 0-10Vdc or 4-20mA signal on proportioning models.



MAR Series Actuator

VALVE ACTUATOR ORDERING INFORMATION		
ORDER#	SIGNAL	FOR VALVE
AM24	On/Off	2", 2-1/2"
AM24-SR	Prop	
GM24	On/Off	3", 4", 5", 6"
GM24-SR	Prop	
MAR100-16	On/Off	8", 10"
MAR100-16-P	Prop	
MAR160-16	On/Off	12"
MAR160-16P	Prop	