

FAX 610-789-7300

WWW.NECCDELIVERS.COM

800-227-9800



NEW! Solar Powered Industrial Thermometer With Digital Display

The bulb and socket are completely interchangeable with standard industrial thermometers. Fits right back into your existing well. The easy to read LCD display has a range of -40 to 300°F and -50 to 150°C (user selectable). Reads to 0.1 of a degree. Large solar panel needs only 10 lux (1 foot/candle) to operate. Adjustable stem makes it easy to read at any angle.

| ORDERING INFORMATION | | | |
|----------------------|---------------------|------------------------|--|
| STEM | ORDER # (with well) | ORDER # (without well) | |
| 3.5" | D010301 | D010300 | |
| 6" | D010601 | D010600 | |




NEW! Solar Powered Digital Display Industrial Airstream Thermometer

Features:

- Includes reversible duct flange
- Dual digital range: -40 to 300°F and -50 to 150°C
- · Adjustable angle for easy reading
- · Cost competitive to mercury models
- · Faster response
- Reads to 0.1°F

| ORDERING INFORMATION | | |
|----------------------|---|--|
| ORDER# | DESCRIPTION | |
| D010304 | Digital Air Duct Thermometer with 3.5" Stem | |
| D010604 | Digital Air Duct Thermometer with 6" Stem | |



3" Round Dial Face Digital Thermometers

Directly replaces many analog bimetal dial thermometers. Stem sizes available from 2.5" to 24". Stock sizes are shown on the chart below.

Features:

- Weather resistant, hermetically-sealed 304 S.S. case
- · Safety circuit to prevent false readings
- -50 to 300°F range
- 15 second update
- Accuracy of 1% of scale

| ORDERING INFORMATION | | | |
|----------------------|--------------------------|----------------------------|--|
| STEM | ORDER # (back connected) | ORDER # (adjustable angle) | |
| 2.5" | 80025A2G4 | 82025A2G4 | |
| 4" | 80040A2G4 | 82040A2G4 | |
| 6" | 80060A2G4 | 82060A2G4 | |