

Standard Clamp-on Digital Multimeter

This clamp-on meter measures current, line and control voltages, relays, resistors and continuity with DCV, ACV, ACA and resistance ranges at a budget price. Includes test leads, 9V battery and hard carrying case.

Features:

- 3.5" digit LCD with 1/2" numerals
- Data and peak hold
- Overload protection to 1000V
- Low battery indication
- Automatic zero
- Base accuracy $\pm 1.5\%$ ± 3 digit

ORDERING INFORMATION

ORDER #	DESCRIPTION
DCP9	Clamp-on meter with case



Digital Clamp-on Adapter

This digital clamp-on adapter is compatible with most multimeters that have a 200mV, 2V, or 400mV range (ac/dc).

Ranges:

AC amps: 40,400
DC amps: 40,400

Accuracy:


40A: $\pm 1.5\%$ of reading + 2 digits
400A: $\pm 1.5\%$ of reading + 4 digits

Output:

AC amps: 1mV AC per 1A
DC amps: 1mV AC per 1A

ORDERING INFORMATION

ORDER #	DESCRIPTION
CA30	Clamp-on adapter for digital multimeters



TA1K

Digital Multimeter Accessories

TA1K Temperature Adapter

K-type thermocouple temperature adapter for digital multimeters with 200mV and/or 2Vdc ranges. Plugs directly into COM and DCV/ohm input jacks. A battery and 4 ft. temperature probe are included (works with **DM383** and **DM420**).

ACO100 Carbon Monoxide

Attachment allows you to measure basic CO concentrations with most multimeters. Use with any 3.5" digit DMM or clamp-on meter with 2 or 4Vdc range and 10Mohm impedance (works with **DM383**, **DM420**, **DL297T** and **DL90A**).



ATLFSG



ACO100

ATLFSG Flame Safeguard Test Kit

Used with DMM's having 20 μ A or 200 μ ADC ranges. It troubleshoots most flame safeguard controls with 3.5mm input jacks. Includes probes and alligator clips (works with **DM420** and **DL297T**).

FLK1 Fused Lead Kit

Allows safer measurements with larger probes so you can keep your distance from dangerous test points. Fused test leads interrupt the current if total or partial grounding occurs between the test leads and the meter.



FLK1

ORDERING INFORMATION

ORDER #	DESCRIPTION
TA1K	Temperature adapter K-type thermocouple with 4 ft. probe
ACO100	CO monitor adapter; 0 to 1999 ppm
ATLFSG	Flame safeguard kit
ATL231	Alligator clips with leads
FLK1	Fused lead kit
AAC	Alligator clips (push-on)