

New state-of-the-art design Quincy Compressors specifically built for the climate control market

- Fast and easy installation
- Saves expensive labor costs

FEATURES:

- ASME coded and National Board approved receiver tank
- ASME coded safety relief valve
- Pressure gauge
- Manual shutoff valve at tank discharge
- High-efficiency motors

Optional Factory Mounted Accessories:

- Available with factory mounted air dryer
- Hankison dryer and pressure regulator
- Coalescing filter and gauges
- Mounted and wired control panel



Simplex Compressor
(Shown Without Dryer)



Duplex Compressor
(Shown With Factory-Mounted Dryer)

QUINCY SIMPLEX						
ORDER #	HP	RPM	Tank	SCFM	SCIM	Weight
QC00503S	1/2	539	30	4.4	7603	225
QC01006S	1	511	60	5.0	8640	480
QC01506S	1-1/2	431	60	6.5	11232	399
QC02006S	2	520	60	9.8	16934	402
QC03008S	3	647	80	12.2	21081	450
QC05012S	5	692	120	18.2	31449	780
QC07512S	7-1/2	604	120	37.5	61690	810
QC10012S	10	682	120	41.2	71194	835
QC15020S	15	605	200	77.0	133056	2544
QC20020S	20	680	240	86.6	149644	2601
QC25020S	25	832	240	106.0	183168	2744

QUINCY DUPLEX						
ORDER #	HP	RPM	Tank	SCFM	SCIM	Weight
QC00503D	1/2	539	30	4.4	7603	340
QC01006D	1	511	60	5.0	8640	520
QC01506D	1-1/2	431	60	6.5	11232	795
QC02008D	2	520	80	9.8	16934	871
QC03008D	3	647	80	12.2	21081	881
QC05020D	5	692	200	18.2	31449	1340
QC07520D	7-1/2	604	200	35.7	61690	1696
QC10024D	10	682	240	41.2	71194	1780
QC15024D	15	605	240	77.0	133056	3200
QC20024D	20	680	240	86.6	149644	3307
QC25024D	25	832	240	106.0	183168	3450
QC25040D		832	400	106.0	183168	3600

Don't Forget—Order you air dryer either factory-mounted or shipped separately.