

RIBM24PL

4" Track-Mount Relay 20 Amp DPST-NO with 24Vac/dc Coil



Functional Devices, Inc. A600 2003




GENERAL SPECIFICATIONS

Relays & Contact Type: One (1) DPST Continuous Duty Coil
Expected Relay Life: 10 million cycles minimum mechanical
Operating Temperature: -30 to 140° F
Relay Status: LED On = Activated
Dimensions: 2.35" x 4" x 2.75"
Approvals: UL Listed, UL916, UL864, C-UL Canada
California State Fire Marshal
Gold Flash: Yes
Override Switch: No


CONTACT RATINGS

20 Amp resistive	300 Vac
20 Amp resistive	28 Vdc
15 Amp resistive	600 Vac
1 HP	120 Vac
2 HP	240-277 Vac
3 HP	480-600 Vac
20 Amp Ballast	277-480 Vac
770 VA Pilot Duty	120 Vac
1,158 VA Pilot Duty	240 Vac
1,110 VA Pilot Duty	277 Vac
1,640 VA Pilot Duty	480 Vac

CONTROL INPUT



CONTACT OUTPUT



COIL CURRENT

100 mA @ 20 Vac	50 mA @ 20 Vdc
125 mA @ 24 Vac	50 mA @ 24 Vdc
	70 mA @ 30 Vdc

COIL VOLTAGE INPUT

24 Vac / dc; 50-60 Hz
DROP OUT = 3 Vac / 3.8 Vdc
PULL IN = 20 Vac / 20 Vdc

NOTES

Can be ordered Normally Closed by adding
"-NC" to the end of the model number

NOTES: